

Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P: 9210 903 903, +91 129 4272727, S 93111 24302 E: info@prestogroup.com



Faridabad
 Sonipat
 Kolkata
 Mumbai
 Pune
 Ahmedabad
 Chennai
 Bangalore
 Hyderabad

www.prestogroup.com

Top Load Tester- Digital with NITRO LCD




Model No. PTL-0105

Registered Design No. 279112

Top Load Tester – Digital is a new generation semi automatic motorized top load tester. It gives Compressive Buckling Load in digital format. The digital display is a high end sophisticated read out with Auto Tare (ZERO) set facility and Peak Hold arrangement. The test sample is placed in between the inverted concave jaws for zero slip gripping.

- Capacity: 100 Kgf
- Speed: Fixed as per standard.
- Grip to Grip Separation: Min. 25mm & Max. 500mm.
- Sample Platform Size: Ø 180 mm x Height 450 mm
- Microprocessor based LCD display for accurate test results $\pm~1\%$
- After completion the test auto home return
- TARE and Peak Hold Facility Available
- Over travel protection
- Memory for retaining peak value automatically





Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India

P: 9210 903 903, +91 129 4272727,

93111 24302 E: info@prestogroup.com • Faridabad • Sonipat • Kolkata • Mumbai • Pune • Ahmedabad

> · Chennai · Bangalore · Hyderabad www.prestogroup.com



Top Load Tester is designed to provide Compressive buckling load. The instrument is used for testing the load bearing capacity of the PET containers when subjected to an extreme load from the Top direction. It determines accurately the maximum load a PET container can bear without any deformation or failure.

Key Specifications:

| Model available in various Load Range | 100Kgf (50 Kgf on request) |
|---------------------------------------|---|
| Accuracy | ± 1% full scale (with master load) |
| Least Count/Resolution | 0.01 Kgf |
| Test Speed * | 24±5 mm / min. |
| Difflection | 1 mm Least count |
| Power | 220 V, Single phase, 50 Hz |
| Display | LCD Display 2 column |
| Load Monitoring | Peak Load indicator with Digital readout and peak hold feature. |
| Compression Plate | Dia of Compression Plate - 180 mm ± 5mm |

^{*} VFD drive optional for variable speed.

Highlights:

| Auto Test Stop | Yes |
|------------------|--|
| Auto Home Return | Yes |
| Safety | Upwardand Down ward Limit switches provided (over travel safety) |
| Grips | Invertedstraight Compression Plates 1 set |
| Material | Mild Steel |
| Finish | Powder coated Havel Gray & Blue combination finish and bright chrome / zinc plating for corrosion resistant finish |
| Dimensions | 635 x 583 x 1161 mm |
| Safety | Over load protection set at 80% of max. load value |

Optional Features:

- Top Load Tester Digital cum Computerized model also available
- Top Load Tester Prima Series with Touch Screen model also available

Thank you customers for choosing us as your partners in growth!



























OUR OTHER PRODUCTS:-













Top Load Tester

Wall Thickness Gauge

Top Load Tester for Jar

Secure Seal Tester HMI

Moisture Analyzer MB 45

Preform Neck Cutter

^{*}All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.